

MICROMETER ADJUSTABLE TORQUE WRENCHES

Metal Handle Dual Scale. The metal handle series offers the user a rugged, industrial strength torque wrench able to withstand the rigors of professional use. Handles are lightly knurled for a tough, non-slip grip. There are 21 models of metal handle micrometer adjustable torque wrenches available.


Features

- Dual scale, calibrated dual direction
- Positive lock with spring loaded pull down lock ring
- Fast, accurate and easy to set
- Easy-to-read laser marked scales
- Most feature quick release buttons which provide good socket retention as well as easy socket removal
- Accuracy: ± 4% clockwise ± 6% ccw of indicated value, cw, from 20% to 100% of full scale
- Meets or exceeds ASME B107.14-2004, ISO 6789 standards
- Individually serialized with matching certificate of calibration traceable to N.I.S.T.



▶ Visit us at Transcat.com!

35 Vantage Point Drive Rochester, NY 14624
Call 1.800.800.5001




MICROMETER ADJUSTABLE TORQUE WRENCHES - DUAL SCALE

Product Code	Drive Size	Torque Range SAE	Incr.	Torque Range Newton Meter	Incr.	A In.	B In.	C In.	D In.
501MRMH	1/4"	10-50 in. lb.	1	1.4 - 5.4	.06	10.15	1.06	0.93	1.06
1502MRMH	3/8"	20-150 in. lb.	1	2.8 - 15.3	.12	10.15	1.06	0.93	1.06
2002MRMH	3/8"	30-200 in. lb.	1	4.0 - 22.0	.12	10.15	1.06	0.93	1.06
2502MRMH	3/8"	30-250 in. lb.	1	4.0 - 27.7	.12	11.25	1.06	0.93	1.06
7502MRMH	3/8"	100-750 in. lb.	5	14.1 - 81.9	.6	16.00	1.43	1.20	1.40
10002MRMH	3/8"	150-1000 in. lb.	5	19.8 - 110.2	.6	16.00	1.43	1.20	1.40
25003MRMH	1/2"	300-2500 in. lb.	10	39.6 - 276.9	1.2	18.00	1.70	1.40	1.40
752MFRMH	3/8"	5-75 ft. lb.	0.5	10.2 - 98.3	.7	16.00	1.43	1.20	1.40
1002MFRMH	3/8"	10-100 ft. lb.	0.5	16.9 - 132.2	.7	16.00	1.43	1.20	1.40
1503MFRMH	1/2"	20-150 ft. lb.	1	34 - 197	1.4	19.00	1.70	1.40	1.40
2503MFRMH	1/2"	30-250 ft. lb.	1	47 - 332	1.4	24.40	1.70	1.40	1.40
4004MFRMH	3/4"	80-400 ft. lb.	5	85 - 491	3.4	34.25	2.50	2.10	1.40
6004MFRMH	3/4"	100-600 ft. lb.	5	169 - 779	6.8	42.00	2.50	2.00	1.15
10005MFRMH*	1"	200-1000 ft. lb.	5	305 - 1322	6.8	70.00	3.00	3.00	1.50
20005MFMH**	1"	300-2000 ft. lb.	10	474 - 2643	14	108.50	3.15	4.25	1.65

*NOTE: 10005MFRMH supplied with one extension handle and is packed in a metal box.

**NOTE: 20005MFMH supplied with two extension handles, fixed/non-ratcheted head and is packed in a sturdy cardboard box.



TORQUE TOOLS

