

Product DATASHEET

Big Digit Hygro-Thermometers

Simultaneous display of Temperature and Humidity

Visit us at Transcat.com!

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001

Features:

- Attractive design for desktop or wall mounting
- Large LCD displays of Temperature and Humidity
- Max/Min memory with reset for Temperature and Humidity
- Switchable °C or °F temperature units
- · Complete with built-in tilt stand, wall mounting bracket and AAA battery

445713 Additional Features

- Dual indoor/outdoor Temperature and Humidity displays
- Remote "outside" sensor on 35" (89cm) cable

445715 Additional Features

- Remote sensor on 35" (89 cm) cable
- User accessible temperature and humidity calibration adjustments
- Available with a NIST traceable certification
- · Optional RH calibration bottles

ϵ

Specifications:	445703	445713	445715
Humidity range	10 to 99%RH	10 to 99% RH	10 to 99% RH
Basic RH accuracy	± 5% (25 to 85%)	± 5% (25 to 85%)	± 4% (25 to 85%)
Temperature range	14 to 140°F (-10 to 60°C)	14 to 140°F (-10 to 60°C)	14 to 140°F (-10 to 60°C)
Basic Temperature Accuracy	±1.8°F/1°C (14 to 122°F)	±1.8°F/1°C (14 to 122°F)	±1.8°F/1°C (14 to 122°F)
Dimensions	4.3x3.9x0.78"(109x99x20mm)		
Weight	6 oz (169g)		

445580-C Optional calibration salt bottles for 445715





445713 Big Digit Indoor/Outdoor Hygro-Thermometer



445715 Big Digit Remote Probe Hygro-Thermometer





