


Pomona®

Model 4911A Retractable Sheath Banana Plug Each End Patch Cord



MATERIALS:

Retractable Sheath Banana Plug:

Plug Body: Brass, Nickel Plated

Banana Spring: Beryllium Copper, Nickel Plated

Compression Spring: Stainless Steel

Tip: Nylon, Color Matches Color of Wire

Insulation: Nylon Molded to the Plug and Wire. Color Matches Color of Wire.

Wire: 18 AWG, Stranding 65 x 36 t.c., PVC Insulated, .144 (3,66mm) O.D.

Marking: "POMONA 4911A-XX-*".

RATINGS:

Operating Temperature: +55° C (+131° F) Max.

Operating Voltage: 1000 Volts AC/DC Max.

Current: 10 Amperes

ORDERING INFORMATION: Model 4911A-XX-*

XX = Wire Length, Standard Lengths: 4" (10,16cm), 8" (20,32cm), 12" (30,48cm), 24" (60,96cm), 36" (91,44cm), 48" (121,92cm) & 60" (152,4cm). Additional lengths can be quoted upon request.

* = Color, -0 Black, -2 Red

Ordering Example: 4911A-12-2 Patch Cord is 12" (30,48cm), Color is Red.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA