





## **FEATURES:**

- ✓ Converts BNC (male) cables / connectors to a #8 spade lug connector for terminal strip attachment.
- ✓ BNC connector is molded directly to the wire for pull strength durability and dust and moisture resistance.
- ✓ BNC shell is tarnish resistant.
- ✓ BNC center contact is gold plated Beryllium Copper for excellent electrical connection.
- ✓ Black wire is connected to BNC shell, red wire to BNC center contact.

## **MATERIALS:**

BNC: Nickel Plated Brass, Center Contact: Gold Plated Beryllium Copper Dielectric: PTFE
Wire: 20 AWG, PVC
#8 Spade Lug: Tin-plated copper alloy
Lug Insulation: Vinyl, color matches color of wire

## **RATINGS:**

Operating Voltage: Hands free testing in controlled voltage environments: 500VRMS Max. Operating Temperature: +131°F (+55°C) Max.

## ORDERING INFORMATION: Model 5051

\* Custom lengths are available, contact Pomona Product Support at: 1-800-241-2060

All dimensions are in inches. Tolerances (except noted):  $.xx = \pm .02^{\circ}$  (,51 mm),  $.xxx = \pm .005^{\circ}$  (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.

