

725 Pocket Combustible Gas Detector

APPLICATIONS

- Trace natural gas lines and fittings for leaks.
- Check gas applications for leaks.
- Check propane tanks, fitting lines, and heaters for leaks.
 - Check gas generators for fuel leaks.
- Test confined spaces for gas build-up.




Actual size

725 Features

- Detects Combustible Gases Including: Natural Gas, Methane, Butane, Propane(LPG), Gasoline, Diesel, and Kerosene
- Fits in shirt pocket
- Auto zeros
- Visual and audible alarm
- Responds instantly

LEAK LEVELS



Level 4: > 5,000ppm Methane

Level 3: > 4,000ppm Methane

Level 2: > 2,000ppm Methane

Level 1: > 1,000ppm Methane

Power: Green = Ready Red = Replace Batteries

Turn over for technical information and accessory part numbers.

The Value Leader™

OPERATING INSTRUCTIONS

- Remove sensor cap
- Press ON/OFF button
- LEDs will flash as the unit initializes; when the green LED above the ON/OFF button is lit, the unit is ready
- Upon detection an alarm will sound & the red LED will indicate the severity of the leak





TECHNICAL SPECIFICATIONS AND ACCESSORIES

Digital
Multimeters •
Clamp Meters •
Hand-held
Oscilloscopes •
Refrigerant &
Combustible Gas
Leak Detectors •
Temperature
Testers • BNC
Coax Cable •
Connectors •

Test Leads •

Accessories

725 Pocket Combustible Gas Detector

Instrument Specifications

Sensitivity:	> 1,000ppm combustible gas (Methane)
Operating Temp:	32° to 104°F (0° to 40° C)
Warm-up:	7-10 seconds
Response Time:	Instantaneous
Battery:	Two AAA
Power Consumption:	DC 20mA
Battery Life:	3 continuous hours
Overall Dimensions:	1.38" 5.0" x 0.75" (34.9 x 127 x 19.1)
Weight:	0.30 lb. (0.14 kg.)

Distributed By:





35 Vantage Point Drive Rochester, NY 14624 Call 1.800.800.5001

