Manual Supplement

Manual Title: 233 Calibration
Part Number: Web-only
Print Date: October 2009

Supplement Issue: 2
Issue Date: 4/14
Page Count: 1

Revision/Date:

This supplement contains information necessary to ensure the accuracy of the above manual.



233 Calibration Manual Supplement

Change #1, 63818, 65340

On page 3, add the following to the Symbols table:

	Conforms to relevant South Korean EMC Standards.		
C	Conforms to CAN/CSA-C22.2 No. 61010-1, second edition, including Amendment 1.		
CAT II	Measurement Category II is applicable to test and measuring circuits connected directly to utilization points (socket outlets and similar points) of the low-voltage MAINS installation.		
CAT III	Measurement Category III is applicable to test and measuring circuits connected to the distribution part of the building's low-voltage MAINS installation.		
CAT IV	Measurement Category IV is applicable to test and measuring circuits connected at the source of the building's low-voltage MAINS installation.		

On page 3, under *General Specifications*, remove *Electromagnetic Compatibility*, *Safety Compliance* and *Certifications* and add:

Electromagnetic Compatibility	In an RF field of 3 V/m, accuracy = specified accuracy except in temperature: specified accuracy ±5 °C (9 °F) FCC ID T68-F233 IC: 6627A-F233		
Applies to use in Korea only	Class A Equipment (Industrial Broadcasting & Communication Equipment) [1] This product meets requirements for industrial (Class A) electromagnetic wave equipment and the seller or user should take notice of it. This equipment is intended for use in business environments and is not to be used in homes.		
Safety	IEC 61010-1: Pollution Degree 2 IEC 61010-2-030: 600 V CAT IV / 1000 V CAT III		

Change #2

On page 13, Table 3, replace step 18 with:

18	V Hz AC Volts + Hz	6.000 V	2 V, 50 kHz ^[1]	49.97 to 50.03
----	---------------------------	---------	----------------------------	----------------

4/14 1