

Hydraulic Hand Pumps with Gauge Connection HPGV (3000 psi / 210 bar), XHGV (5000 psi / 350 bar)

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001

Fast and efficient hydraulic field testing of pressure transmitters, gauges or switches is aided by an integral gauge adapter which allows the user to quickly attach a precision test gauge to the pump.

Features:

- Portable, hand operated hydraulic pumps that easily generate up to 5000 psi (350 bar)
- Fine adjustment piston provides an easy way to fine tune exact pressure
- Bleed pressure slowly with soft seated vent valve
- Liquid reservoir holds enough fluid for multiple calibrations
- Marine brass construction resists corrosion and abuse
- Quick-disconnect gauge adapter allows changing gauges without using a wrench
- Low volume Quick-test hose, gauge adapter and process connection can be attached to pump without thread sealant or a wrench
- Made in U.S.A.



(Reference gauge not included)

Specifications		
Pump connection type	National Pipe Thread (NPT)	British Parallel Thread (BSPP)*
Pressure media	Ralston calibration oil (QTHP-HYDL), mineral based oil, hydraulic oil, water	Ralston calibration oil (QTHP-HYDL), mineral based oil, hydraulic oil, water
Fine adjust resolution	± 1 psi (0.1 bar)	± 1 psi (0.1 bar)
Reference connection (brass)	1/4" female NPT swivel (SWIV-2FBW)	1/2" female BSPP swivel (SWIV-4GBW)
HPGV outlet port (brass)	Male Quick-test with check-valve (QTHA-3SB1)	Male Quick-test with check-valve (QTHA-3SB1)
XHGV outlet port (brass)	Male Quick-test with cap and chain (QTFT-3SB0)	Male Quick-test with cap and chain (QTFT-3SB0)
Calibration hose (brass ends)	3 ft (92 cm) long (QTQT-HOS-3')	1 m (3.3 ft) long (QTQT-HOS-1m)
Process connection (brass)	1/4" male NPT (QTHA-2MB0)	1/4" female BSPP (QTHA-2FB0-RG)
Liquid reservoir	7.2 fl oz (256 ml) clear polycarbonate (QTHP-RESV)	7.2 fl oz (256 ml) clear polycarbonate (QTHP-RESV)
Construction	Brass, aluminum, plated steel	Brass, aluminum, plated steel
Seal material	Buna-N, Teflon™, Delrin™, synthetic cork	Buna-N, Teflon™, Delrin™, synthetic cork
Bottle included	12 fl oz (355 ml) with flip-up top, empty	12 fl oz (355 ml) with flip-up top, empty
Weight	2.6 lb (1.2 kg)	2.6 lb (1.2 kg)

Ordering information	
HPGV, XHGV pumps with brass NPT connections	
Model	Description
HPGV-0000	3000 psi (210 bar) pump, hose, NPT gauge swivel and process connection
XHGV-0000	5000 psi (350 bar) pump, hose, NPT gauge swivel and process connection
HPGV, XHGV pumps with brass BSPP connections*	
Model	Description
HPGV-4GBW	3000 psi (210 bar) pump, hose, BSPP gauge swivel and process connection
XHGV-4GBW	5000 psi (350 bar) pump, hose, BSPP gauge swivel and process connection

* Not for sale in North American market
For hoses and accessories see page 17. For a complete list of accessories and parts see product manual or detailed specification sheet.
For a list of the most commonly used gauge and process connections see page 18. For a complete list refer to Ralston Instruments Pressure Connection catalog. Contact your Ralston Instruments dealer or the factory for information on reference gauges and pressure calibration kits.

TRANSCAT

35 Vantage Point Drive
Rochester, NY 14624
1.800.800.5001

▶ Visit us at Transcat.com!