

TRANSCAT

▶ Visit us at Transcat.com!

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001

All Products

Automotive Products

Basic Electrical Testers

Cable Testers

Calibrators

Clamp Meters

Comm. Test Tools

Data Acquisition

Digital Multimeters

Gas Measurement

Network Products

Power Supplies

Oscilloscopes

RCL Meters

Process Products

Power Quality Tools

ScopeMeters

Thermometers

Signal Sources

Timer/Counters

TV Generators

i200s Current Clamp

[[Product Home](#)]



Small sized,
convenient-to-use
current clamp

The i200s is a dual range 20A and 200A ac current clamp with voltage output via a safety insulated BNC connector. A dual banana to BNC adapter is supplied to allow the i200s to be connected to multimeters with banana inputs.

- Measuring range: 0.1 to 24A and 0.5 to 240A
- The output signal is 100 mV/A in the 20A range and 10 mV/A in the 200A range
- Includes BNC connector making it suitable for use with any oscilloscope, power analyzer or ScopeMeter™ test tool having a compatible BNC input connector
- Dual banana to BNC adapter is included for use with DMMs
- Maximum current 240A ac
- 40 Hz to 10 kHz frequency response
- Jaw opening 21 mm
- Maximum conductor size 20 mm dia. or busbar 20 x 5 mm
- EN61010, CAT III 600V
- One year warranty

TRANSCAT

▶ Visit us at Transcat.com!

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001

© 1995 - 1999 Fluke Corporation

[Privacy Statement](#)