



TRANSCAT®

[Visit us at Transcat.com!](http://Transcat.com!)

35 Vantage Point Drive Rochester, NY 14624
Call 1.800.800.5001



OTS®

SPECIAL FEATURES:

- Lightweight nylon temples adjust for length and pitch.
- Lenses are coated for superior scratch resistance.
- Lenses provide 99% protection against harmful UV rays.
- Designed to better fit today's prescription eyewear.
- Single lens encapsulates the eye for superb protection.

GENERAL SPECIFICATIONS

Lens Thickness:	2.03mm	PD	68 mm
Lens Base	2.0 curve	Weight	33 gm
Lens size vertical	49.5mm	Lens Size Diagonal	58.4 mm
Bridge	19.5mm	Temple length (lens-tip)	152-166mm

Overall Width (hinge-hinge)	148mm
Closest point between lens	13.9
Closest point between temple tips	82, 80mm

FRAME AND LENS OPTIONS:

Temple colors:	Black
Lens options:	Clear Anti-fog, Gray, I/O Mirror

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Wraparound with angle side protection
Side Shield	Polycarbonate	Angled
Nose piece	Polycarbonate	Universal, Integral to lens
Angle Adjust	Nylon	Ratchet type
Sleeve	Nylon	4 lengths positions adjustment
Temple Tip	PVC	Spatula, Soft & Extendable
Hinge	Nylon	3 barrel type
Screw	Stainless Steel Standard hinge screw	

MARKINGS

Lens: As per standard
Frame: As per standard

PACKAGING

1 pc in a polybag; 12 pcs in an inner box; 300 pcs in a case

STANDARDS

MEETS ANSI Z87.1 STANDARDS AND CE EN 166 CERTIFIED
TEST RESULTS AVAILABLE UPON REQUEST

TRANSCAT®

[Visit us at Transcat.com!](http://Transcat.com!)

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001