

# LIGHTS

## 9430

### Remote Area Lighting System



### 9430 Remote Area Lighting System

- Up to 15 hours of burntime
- 2000 lumens of brightness
- Maintenance Free LED Array with life expectancy of 50,000 hours
- Fully extendable mast with 360 degree rotating head
- Low Battery Warning System
- Waterproof Rubber Activation Switch
- Mast Extension Lock

### 9430 Remote Area Lighting System Configurations

Cat. #	Description
9430	9430 Remote Area Lighting System



### 9430 Remote Area Lighting System Specifications

LED Type	LED Life	Tested Lumen Value		
High Flux LED	50000 hrs.	1000 (Low) 2000 (High)		
Lamp Heads	Number of LEDs	Beam Spread	Brightness Settings	
1	24	90 degrees	2	
Battery Type	Battery Burn Time	Battery Charging Time	Battery Life	Low Battery Warning
12v Rechargeable, Sealed	15 hrs. (Low) 8 hrs. (High)	7 hrs. from full discharge	2000 cycles	Intermittent Blinking
12 Volt Primary Sockets	12 Volt Auxiliary Sockets		Watts	Voltage
1	1		24	12
Head Material	Body Material		Mast Material	
Polycarbonate/ABS	Polycarbonate/ABS		Glass-Reinforced Plastic	
Lens Material	Switch Type Material			
Polycarbonate	Silicone rubber keypad			

Head Length	Head Width	Head Depth
6.5" (16.5 cm)	7.87" (20 cm)	2.56" (6.5 cm)
Width Closed	Length Closed	Height Closed
7.87" (20 cm)	15.75" (40 cm)	9.06" (23 cm)
Mast Height Extended	Cord Length	Weight
32.28" (82 cm)	13.78" (35 cm)	22.05 lbs. (10 kg)

## 9430 Remote Area Lighting System Approvals

RoHS (Restriction of Hazardous Substances) Compliant

## 9430 Remote Area Lighting System Accessories

Cat. #	Description
9436	12/24V Vehicle Charger
9432	9430 Back Pack
9431	9430 Tear-Off Back Pack
9435	Spare LED Head including Mast
9438	9430 RALS Universal Charger
9430T	9430T Tripod Kit
9437	Extension Cord 118 inches (3m)