



FEATURES:

- Provides a larger working area than Model 6087
- This kit provides a static-safe 22" x 24" laminated red vinyl mat
- The mat includes a 10mm snap socket and two 8" x 11" pockets.
- Carry those often used tools right with the mat
- A common point ground connector with two Banana Plug Jacks and a 15' ground lead
- An adjustable elastic wrist strap and a resistive coil cord completes the kit
- Folds down to fit into your tool box

MATERIALS:

Anti-Static Ground Cord

Body: Plug – Brass, nickel plate, fits 4,2 (.17) standard Banana Jack

Insulation: Banana Plug – Thermoplastic elastomer, Black

Cord: Coiled Tinsel Cord, vinyl jacket, 2,5 (.10) O.D.

Body: Snap – Brass, nickel plate, fits 4,0 (.16) snap stud

Insulation: Snap – Thermoplastic elastomer, Black

Wrist Strap

Body: Impact resistant plastic, Blue

Strap: Elastic fibers with silver plated Nylon, Yarn, Circumference: 64,0 (2.50) min., 330,0 (13.00) Max.

Snap and Cam: Stainless Steel, 4,0 (.16) snap stud

MAT, ESD: 0,46 (.018") thick, vinyl, Red

Common Point Ground Cord

Snap W/Banana Jacks End:

Body: Snap – Brass, Nickel Plate. 10,0 (.39), Male

Resistor: One Megohm resistor, insulated

Insulation: Snap – Thermoplastic elastomer, Black

Cord: 22 AWG, vinyl jacket, 2,5 (.10) O.D., Length: 46,0 (17.0)

Banana Jacks: Brass, Nickel plated. Fits 4,2 (.17) Standard Banana Plug

Large Alligator Clip End:

Body: Alligator Clip – Brass, Nickel Plate, fits 4,2 (.17) Standard Banana Plug

Insulation: PVC, Black

RATINGS:

Surface Resistivity: 108 to 109 Ohm/Sq.

Volume Resistivity: 109 Ohm cm

Static Decay: 0.01 sec 5000V to 0V 12% RH

ORDERING INFORMATION: Model 6088

Packaging: One Anti-Static ground cord, common point ground cord, Mat, Wrist strap, and two instruction sheets, per bag

TRANSCAT[®]

 [Visit us at Transcat.com!](http://Transcat.com)

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001