

Patch Cords and Test Leads



®




Pomona
ACCESS

FAX ON DEMAND This symbol indicates immediate Fax-On-Demand Technical Information is available. Dial (U.S.) (800) 444-6785, (Outside U.S.) (949) 253-3858. Enter the Pomona Access number (shown in italics) when prompted.

Patch Cords and Test Leads

MULTI-STACKING BANANA PLUG PATCH CORD



Model B Multi-Stacking Banana Plug Patch Cord features a nickel plated finish.
18 AWG Wire, .144 O.D.
RATING: 5000 VDC, 15 Amps, +55°C (+131°F) Max.
*STD COLORS: Available in 10 Colors.

<i>Pomona ACCESS</i>	Part No.	Length
90534	B-4-*	4"
	B-8-*	8"
	B-12-*	12"
	B-18-*	18"
	B-24-*	24"
	B-36-*	36"
	B-48-*	48"
	B-60-*	60"
	B-72-*	72"

Model 2948 Multi-Stacking Banana Plug Patch Cord features a gold plated finish.
*STD COLORS: -0 blk, -2 red.

<i>Pomona ACCESS</i>	Part No.	Length	Special Features
90534	2948-12-*	12"	Gold Plated Finish
	2948-24-*	24"	
	2948-36-*	36"	
	2948-48-*	48"	
	2948-60-*	60"	


CROSS STACKING BANANA PLUG PATCH CORD



18 AWG Wire, .144 O.D.
RATING: 5000 VDC, 15 Amps, +55°C (+131°F) Max.
*STD COLORS: -0 blk, -2 red.

<i>Pomona ACCESS</i>	Part No.	Length
90544	1440-8-*	8"
	1440-12-*	12"
	1440-18-*	18"
	1440-24-*	24"
	1440-36-*	36"
	1440-48-*	48"
	1440-60-*	60"

HORIZONTAL STACKING BANANA PLUG PATCH CORD



18 AWG Wire, .144 O.D.
RATING: 5000 VDC, 15 Amps, +55°C (+131°F) Max.
*STD COLORS: -0 blk, -2 red.

<i>Pomona ACCESS</i>	Part No.	Length
90535	HB-12-*	12"
	HB-24-*	24"
	HB-36-*	36"
	HB-48-*	48"
	HB-60-*	60"

MULTI-STACKING BANANA PLUG COILED PATCH CORD

One patch cord replaces many different lengths.



20 AWG Wire, .087 O.D., Extended Length: 48"
RATING: 3000 VDC Int., 270 VDC, 90 VAC cont. duty, 5 Amps, +55°C (+131°F) Max.
*STD COLORS: -0 blk, -2 red.

<i>Pomona ACCESS</i>	Part No.
90557	2484-*


MULTI-STACKING BANANA PLUG PATCH CORD WITH IN-LINE FUSE HOLDER



18 AWG Wire, .144 O.D.
RATING: 5000 VDC, 15 Amps, +55°C (+131°F)
*STD COLORS: -0 blk, -2 red.

<i>Pomona ACCESS</i>	Part No.	Length
90593	4274-24-*	24"
	4274-36-*	36"


MULTI-STACKING BANANA PLUG TO MINIATURE STACKING BANANA PLUG



20 AWG Wire, .087 O.D.
RATING: 3000 VDC, 5 Amps +55°C (+131°F) Max.
*STD COLORS: -0 blk, -2 red.

<i>Pomona ACCESS</i>	Part No.	Length
90569	3014-12-*	12"
	3014-18-*	18"
	3014-24-*	24"
	3014-36-*	36"
	3014-48-*	48"
	3014-60-*	60"


MULTI-STACKING BANANA PLUG TO STACKING PIN TIP PLUG



20 AWG Wire, .087 O.D.
RATING: 3000 VDC, 5 Amps, +55°C (+131°F) Max.
*STD COLORS: -0 blk, -2 red.

<i>Pomona ACCESS</i>	Part No.	Length
90430	1126-4-*	4"
	1126-8-*	8"
	1126-12-*	12"
	1126-18-*	18"
	1126-24-*	24"
	1126-36-*	36"
	1126-48-*	48"
	1126-60-*	60"

RIGHT ANGLE STACKING BANANA PLUG PATCH CORD



18 AWG Wire, .144 O.D.
RATING: 5000 VDC, 15 Amps, +55°C (+131°F) Max.
*STD COLORS: -0 blk, -2 red.

<i>Pomona ACCESS</i>	Part No.	Length
90559	2864-4-*	4"
	2864-8-*	8"
	2864-12-*	12"
	2864-18-*	18"
	2864-24-*	24"
	2864-36-*	36"
	2864-48-*	48"
	2864-60-*	60"