





## **MODELS**

A-170, Stainless Steel Pigtail Siphon

A-323, Elbow Compression Fitting, brass 1/8" NPT to 1/4" metal tubing

A-324, Compression Fitting, brass 1/8" NPT to 1/4" metal tubing

A-326, Compression Fitting, brass 1/8" NPT to 1/8" tubing

A-327, 5/6" Nylon Tube Union

A-328, 1/4" Nylon Tube Union

A-329, 1/8" N.P.T. Close Coupled Street Ell, Brass

A-330, %" Pipe Plug, socket hex, plated steel

A-331, %" N.P.T Filter Vent Plug, nylon and sintered metal A-332, Bushing, brass, %" to %" NPT A-333, Bushing, brass, %" to %" NPT

A-334, Close Nipple, brass, 1/8" NPT

A-336, 90° Street L, brass, 1/8" NPT

A-337, Coupling, brass, 1/8" NPT

A-338, Servel Adapter, brass %" and %" N.F. Threads for gas appliances to

%" and %6" I.D. rubber or plastic tubing

A-339, Adapter, brass, 1/8" NPT to 1/6" rubber and 1/8" I.D. plastic tubing

A-340, Adapter, nylon, %" NPT to %e" I.D. rubber or %" plastic tubing A-342, "T" Assembly, plastic, for %e" I.D. rubber or %" plastic tubing

A-343, "T" Assembly, plastic, for %" plastic tubing
A-343-1, "T" Assembly, plastic, for %" I.D. plastic tubing
A-344, Terminal Tube, Brass %" diameter tube, 8" length (not shown)

A-345, Flange, aluminum with gasket and sheet metal screws, %" NPT

A-346, "T" Compression Fitting, brass, ¼" metal tubing A-349, Reducer, brass, ¼" female NPT to ½" male NPT

 $\begin{tabular}{ll} $\textbf{A-391}$, Line Filter for Capsuhelic® gage, %" female NPT X \%" male NPT $\textbf{A-392}$, Line Filter for Magnehelic® gage, \%" female NPT x \%" male NPT $\text{NPT}$.$ 

**A-398**, Probe Extension Adapter for series 640 air velocity transmitter. Brass,  $\frac{1}{2}$  female NPT x  $\frac{1}{2}$  compression

**F222**, Liquid/Particle Filter for compressed air. Removes dirt, water and oil. 22 scfm maximum flow, ¼" female NPT inlet and outlet

1201-2, Replacement Filter Element for F222 filter, package of 3

F451, Liquid/Particle Filter for compressed air. Removes dirt, water and oil. 45 scfm maximum flow,  $\frac{1}{4}$ " female NPT inlet and outlet

1201-3, Replacement Filter Element for F451 filter, package of 3

## Miscellaneous





A-362



A-368



A-369



A-370

## **MODELS**

A-298, Flat Aluminum Bracket for flush mounting Capsuhelic®, 603A, 605, and

A-299, Mounting Bracket, flush mount Magnehelic® in bracket. Bracket is then surface mounted. Steel with gray hammertone epoxy finish

A-300, Flat Aluminum Bracket for flush mounting Magnehelic® gage

A-351, Pinch Clamp to seal rubber tubing, as in a leakage test

A-352, Magneclip, slip on magnetic holder for acrylic plastic gages. Per pair

A-353, Magnetic Mounting. Flat style, secures to flowmeter, etc. with No. 6-32 machine screw and boots insert.

A-354, Magnetic Mounting, Edge style, secures edge of acrylic manometer with No. 10-32 machine screw and boots insert

A-356, Gage plug with retainer loop, polyethylene plastic. For 1/2" I.D. tubing. Slip loop over tubing O.D. and insert plug for seal

A-357, Thermometer and terminal tube holder. Stainless steel wire

A-362, Stand-Hang bracket, aluminum, for Minihelic II gage

A-363, Scale Clamp Bar for No. 1221 Manometer

A-364, Magnet Assembly for No. 1222 Manometers, 2 required (3 required for 1222-36 and M-1000).

A-366, Manometer Cleaning Brush 1/4" O.D. x 21/6" Long. Attach to wire for use

A-367, Table Stand for U-Tube Manometers

A-368, Surface mounting plate, aluminum, for Magnehelic® gage

A-369, Stand-Hang Bracket, aluminum, for Magnehelic® gage

A-370. Mounting Bracket. Flush mount Capsuhelic® gage or Series 600 Transmitter in bracket. Bracket is then surface mounted. Steel with gray hammertone epoxy finish

A-371, Surface Mounting Bracket. Use with Photohelic® on horizontal or vertical surfaces. Also for Capsu-Photohelic® on Vertical only

A-395, Surface Mounting Bracket for Series 602/603 transmitters and Series 4000 Capsuhelic® gages. Steel with gray hammertone epoxy finish

A-397, Step Drill. Rugged Step Drill quickly provides true round holes in thin materials. Ideal for installation of Dwyer Pitot Tubes in sheet metal duct. No centerpunch needed to start. Automatically de-burrs drilled hole. High speed steel. Drills 3/16" through 1/2" holes in 1/16" increments. (Net Price, No Discount Allowed)

A-464, Flush Mount Kit for Magnehelics®

A-465, Flush Mount Space Pressure Sensor

A-497, Surface Mounting Bracket for Minihelic®II gage. Steel with satin black finish



