

CASES
1560
Case



1560 Case



- **Watertight, crushproof, and dust proof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded top and side handles
- Stainless steel hardware and padlock protectors
- 2 level Pick 'N' Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Unconditional Lifetime Guarantee of Excellence
- **Retractable extension handle**
- **Strong polyurethane wheels with stainless steel bearings**

1560 Case Configurations

Cat. #	Description
1560	1560 Case
1560NF	1560 Case (No foam)
1564	1560 Case with Padded Dividers



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request

1560 Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
22.06" x 17.93" x 10.43" (56 x 45.5 x 26.5 cm)		20.37" x 15.43" x 9.00" (51.7 x 39.2 x 22.9 cm)	
Lid Depth	Bottom Depth	Total Depth	
2.00" (5.1 cm)	7.00" (17.8 cm)	9.00" (22.9 cm)	
Weight w/Foam	Weight w/o Foam	Buoyancy Max.	
20 lbs. (9.07 kg)	17 lbs. (7.71 kg)	104 lbs. (47.17 kg)	
Range Temperature	No. of Wheels		
-10 / 210° F (-23 / 99° C)	2		

1560 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280