

Rosemount™ 2140 Configuration Data Sheet

- Select only one of the items provided
- One or more of the listed items can be selected

★ = Default Value

Customer information	
Customer: _____	Contact name: _____
Phone no.: _____	Fax no./email: _____
P.O./reference no.: _____	P.O. line item: _____
Quote no.: _____	Model no.: _____
Customer sign-off: _____	

Tagging
Hardware tag: _____ (21 characters maximum)
<input type="radio"/> Software HART® 5: _____ (8 characters maximum)
<input type="radio"/> Software HART 7: _____ (32 ASCII characters maximum)
Note HART 7 model option must be selected if more than 8 character tag is required. If HART 5 in the model option is selected and more than 8 characters are supplied, then the instrument will be programmed with the last 8 characters only.

Transmitter information
Descriptor: _____
Message: _____

Configuration information	
Media density <input type="radio"/> Low (e.g. propane), 400 kg/m ³ – 600 kg/m ³ <input type="radio"/> Medium (e.g. alcohol), 500 kg/m ³ – 900 kg/m ³ <input type="radio"/> Standard (e.g. water), 800 kg/m ³ – 1300 kg/m ³ ★ <input type="radio"/> High (e.g. acid), 1300 kg/m ³ – 3000 kg/m ³	Sensor operating mode <input type="radio"/> Normal <input type="radio"/> Enhanced - fault= dry <input type="radio"/> Enhanced - fault= wet ★
Alarm current level <input type="radio"/> Low alarm <input type="radio"/> High alarm ★	Current output operating mode <input type="radio"/> Dry = on ★ <input type="radio"/> Wet = on Current output type <input type="radio"/> 4 / 20 mA <input type="radio"/> 8 / 16 mA ★ <input type="radio"/> Level tester <input type="radio"/> Custom ⁽¹⁾ Custom off ⁽³⁾ current _____ mA, Custom on ⁽⁵⁾ current _____ mA
Output delay ⁽²⁾ : _____ seconds★ Fault delay ⁽⁴⁾ : _____ seconds ★	Process temperature (if known): _____ (else 20 °C / 68 °F)
Temperature units: _____ <input type="radio"/> °C ★ <input type="radio"/> °F	

Current output levels				
	Saturation values (Rosemount 2140 with EFP only)		Alarm values	
	Low	High	Low ⁽⁶⁾	High ⁽⁷⁾
Valid range	3.7–3.9 mA	20.0–22.0 mA	3.6–3.8 mA	20.2–23.0 mA
Default range	3.9 mA	20.8 mA	3.75 mA	21.75 mA
Required value				

1. Custom on/off current must be between 4.0–20.0 mA.
2. Output delay range between 0–3600 seconds. (default 1 second).
3. Custom off current must be between 4.0–10.0 mA.
4. Fault delay should be range between 0–3600 seconds. (default 5 seconds).
5. Custom on current must be between 14.0–20.0 mA.
6. Low alarm current must be at least 0.1 mA below the low saturation value.
7. High alarm current must be at least 0.1 mA above the high saturation value.

Global Headquarters

Emerson Automation Solutions

6021 Innovation Blvd.
Shakopee, MN 55379, USA
+1 800 999 9307 or +1 952 906 8888
+1 952 949 7001
RFQ.RMD-RCC@Emerson.com

North America Regional Office

Emerson Automation Solutions

8200 Market Blvd.
Chanhassen, MN 55317, USA
+1 800 999 9307 or +1 952 906 8888
+1 952 949 7001
RMT-NA.RCCRFQ@Emerson.com

Latin America Regional Office

Emerson Automation Solutions

1300 Concord Terrace, Suite 400
Sunrise, FL 33323, USA
+1 954 846 5030
+1 954 846 5121
RFQ.RMD-RCC@Emerson.com

Europe Regional Office

Emerson Automation Solutions Europe GmbH

Neuhofstrasse 19a P.O. Box 1046
CH 6340 Baar
Switzerland
+41 (0) 41 768 6111
+41 (0) 41 768 6300
RFQ.RMD-RCC@Emerson.com

Asia Pacific Regional Office

Emerson Automation Solutions Asia Pacific Pte Ltd

1 Pandan Crescent
Singapore 128461
+65 6777 8211
+65 6777 0947
Enquiries@AP.Emerson.com

Middle East and Africa Regional Office

Emerson Automation Solutions

Emerson FZE P.O. Box 17033
Jebel Ali Free Zone - South 2
Dubai, United Arab Emirates
+971 4 8118100
+971 4 8865465
RFQ.RMTMEA@Emerson.com

Questions?
[Contact Our Rosemount Configuration Specialist](#)



Standard Terms and Conditions of Sale can be found on the [Terms and Conditions of Sale page](#).

The Emerson logo is a trademark and service mark of Emerson Electric Co. Rosemount and Rosemount logotype are trademarks of Emerson. HART is a registered trademark of the FieldComm Group. All other marks are the property of their respective owners. © 2017 Emerson. All rights reserved.