



Model
476A
&
478A

Digital Manometers

Single & Dual Pressure Measurement, Electronic Zeroing, $\pm 1.5\%$ Accuracy

TRANSCAT

▶ Visit us at Transcat.com!

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001

- One-Button Auto-Zero Function
- Auto Power Off.
- Large, Easy-to-Read Display.
- Extruded Aluminum Case.
- Instant Selection from up to Eight English/Metric Units.



Ideal for field or laboratory use, the Model 476A Single Pressure Digital Manometer measures low pressures from -20 to 20" w.c. with $\pm 1.5\%$ full scale accuracy. Designed especially for the HVAC contractor, the Model 476A can be used to set supply pressures, verify pressure switch operation, adjust regulators, check pneumatic systems and computer peripherals. The rugged, hand-held unit is constructed with an extruded aluminum case for exceptional durability.

The Series 478A manometer can be used to measure positive, negative, or differential pressures. The unit features selectable units, auto zero, hold and a Min/Max function. Press the Hold key to freeze the current pressure measurement on the display. The 478A manometer includes a zeroing button to null out any minor pressure differences.

SPECIFICATIONS

Service: Air and compatible gases.

Wetted Materials: Consult factory.

Accuracy: $\pm 1.5\%$ F.S. at 72°F (22.2°C). Includes linearity and repeatability.

Pressure Hysteresis: $\pm 0.1\%$ of F.S.

Pressure Limits: 5 psig (.74 bar).

Temperature Limits: 0 to 140°F (-17.8 to 60°C).

Compensated Temperature Limits: 32 to 104°F (0 to 40°C).

Thermal Effect: 0.05% F.S./°F.

Display: 4 digit LCD (.425"H x .234"W digits).

Power Requirements: 9V alkaline battery. Battery included but not connected.

Process Connections: For use with 3/16" or 1/4" I.D. tubing.

Weight: 10.8 oz (306 g).

Agency Approvals: CE.

476A-0, Digital Manometer, -20 to 20" w.c.

478A-0, Digital Differential Manometer, -4-0-4" w.c.

478A-1, Digital Differential Manometer, -60-0-60" w.c.

A-402A CARRYING CASE — Tough gray nylon pouch protects any Series 476A/478A Manometer. Double zippered for quick and easy access. With belt loop that snaps closed. 7-1/2"H x 3"W x 2-1/4"D (191 x 76 x 57 mm)



Model Number	Range	Available Pressure Units								Resolution in w.c.	Maximum Pressure
		bar	psi	in Hg	kPa	in w.c.	mm Hg	mbar	mm w.c.		
476A-0	-20.0 to 20.0	.0498	0.723	1.471	4.98	20.00	37.4	49.8	508	0.02	5 psig

Model Number	Range in w.c.	Available Pressure Units								Resolution in w.c.	Maximum Pressure
		bar	psi	in Hg	kPa	in w.c.	mm Hg	mbar	mm w.c.		
478A-0	-4.00 to 4.00	.1445	.294	0.996	4.00	7.47	9.96	101.6	996	0.01	5 psig
478A-1	-60.0 to 60.0	.1495	2.168	4.41	14.95	60.0	112.1	149.5	1524	0.1	5 psig

TRANSCAT

▶ Visit us at Transcat.com!

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001