


419S, Anchor Shackles – Screw Pin Drop-Forged Carbon Steel – Self Colored

TRANSCAT®

► Visit us at Transcat.com!

35 Vantage Point Drive Rochester, NY 14624

Call 1.800.800.5001



Size		Cat. No.	UPC No. 020418	Working		Tolerances				Dimensions										Weight/ 100	
in.	mm			Load Limit ton	kg	Length ±in. ±mm	Width ±in. ±mm	B		C		D		E		F		lb	kg		
1/4	6	5410405	076145	1/2	454	1/16	2	1/16	2	5/16	8	1 1/8	29	15/32	12	25/32	20	1 1/16	17	10	5
5/16	8	5410505	076176	3/4	680	1/16	2	1/16	2	3/8	10	1 1/4	32	17/32	13	27/32	21	3/4	19	18	8
3/8	10	5410605	076206	1	907	1/8	3	1/16	2	7/16	11	1 7/16	37	21/32	17	31/32	25	15/16	24	30	14
7/16	11	5410705	076237	1 1/2	1361	1/8	3	1/16	2	1/2	13	1 3/4	44	23/32	18	1 5/32	29	1 1/8	29	52	24
1/2	13	5410805	076268	2	1814	1/8	3	1/16	2	5/8	16	1 15/16	49	13/16	21	1 1/4	32	1 1/4	32	70	32
5/8	16	5411005	076282	3 1/4	2948	1/8	3	1/16	2	3/4	19	2 7/16	62	1 1/16	27	1 9/16	40	1 7/16	37	130	59
3/4	19	5411205	076305	4 3/4	4309	1/4	6	1/16	2	7/8	22	2 13/16	71	1 1/4	32	1 13/16	46	1 3/4	44	200	91
7/8	22	5411405	076329	6 1/2	5897	1/4	6	1/16	2	1	25	3 1/8	79	1 7/16	37	2 1/16	52	2	51	330	150
1	25	5411605	076343	8 1/2	7711	1/4	6	1/16	2	1 1/8	29	3 3/4	95	1 11/16	43	2 1/2	64	2 3/8	60	500	227
1 1/8	29	5411805	076367	9 1/2	8618	1/4	6	1/16	2	1 1/4	32	4 1/4	108	1 13/16	46	2 15/16	75	2 5/8	67	710	322
1 1/4	32	5412005	076381	12	10886	1/4	6	1/16	2	1 3/8	35	4 1/2	114	2	51	3 1/4	83	3	76	1000	454
1 3/8	35	5412205	076404	13 1/2	12247	1/4	6	1/8	3	1 1/2	38	5 1/4	133	2 1/4	57	3 1/2	89	3 1/4	83	1300	590
1 1/2	38	5412405	076428	17	15422	1/4	6	1/8	3	1 5/8	41	5 3/4	146	2 3/8	60	3 7/8	98	3 1/2	89	1600	726
1 3/4	44	5412805	076459	25	22680	1/4	6	1/8	3	2	51	7	178	2 7/8	73	4 3/4	121	4	102	2850	1294
2	51	5413205	076473	35	31752	1/2	13	1/8	3	2 1/4	57	7 3/4	197	3 1/4	83	5 3/4	146	4 7/8	124	4000	1816
2 1/2	64	5414005	076510	55	49896	1/2	13	1/8	3	2 3/4	70	10 9/16	268	4 1/8	105	7 1/4	184	5 1/2	140	9000	4086

Continued on Next Page



ADVERTENCIA

Para prevenir la posibilidad de lesiones graves:

- **NO EXCEDA** el límite de carga de trabajo (WLL).
- **NO LA UTILICE** choque o golpee la carga.
- **NO USE** el accesorio si se ve deformado o desgastado.



WARNING

To prevent the possibility of serious bodily injury:

- **DO NOT EXCEED** the working load limit.
- **DO NOT** shock or impact load.
- **DO NOT USE** if the fitting is visibly distorted or worn.

419-S, Anchor Shackles - Screw Pin continued Drop-Forged Carbon Steel – Galvanized

Size		Cat. No.	UPC No. 020418	Working Load Limit		Tolerances Length		Tolerances Width		B		C		D		E		F		Weight/ 100	
in.	mm			ton	kg	±in. ±mm	±in. ±mm	±in. ±mm	±in. ±mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lb	kg
3/16	5	5410335	076138	1/3	302	1/16 2	1/16 2	1/16 2	1/16 2	1/4 6	7/8 22	3/8 10	19/32 15	9/16 14	5 2						
1/4	6	5410435	076169	1/2	454	1/16 2	1/16 2	5/16 8	1 1/8 29	15/32 12	25/32 20	11/16 17	10 5								
5/16	8	5410535	076190	3/4	680	1/16 2	1/16 2	3/8 10	1 1/4 32	17/32 13	27/32 21	3/4 19	18 8								
3/8	10	5410635	076220	1	907	1/8 3	1/16 2	7/16 11	1 7/16 37	21/32 17	31/32 25	15/16 24	30 14								
7/16	11	5410735	076251	1 1/2	1361	1/8 3	1/16 2	1/2 13	1 3/4 44	23/32 18	1 5/32 29	1 1/8 29	52 24								
1 1/2	13	5410835	076275	2	1814	1/8 3	1/16 2	5/8 16	1 15/16 49	13/16 21	1 1/4 32	1 1/4 32	70 32								
5/8	16	5411035	076299	3 1/4	2948	1/8 3	1/16 2	3/4 19	2 7/16 62	1 1/16 27	1 9/16 40	1 7/16 37	130 59								
3/4	19	5411235	076312	4 3/4	4309	1/4 6	1/16 2	7/8 22	2 13/16 71	1 1/4 32	1 13/16 46	1 3/4 44	200 91								
7/8	22	5411435	076336	6 1/2	5897	1/4 6	1/16 2	1 25	3 3/8 79	1 7/16 37	2 1/16 52	2 51	330 150								
1	25	5411635	076350	8 1/2	7711	1/4 6	1/16 2	1 1/8 29	3 3/4 95	1 11/16 43	2 1/2 64	2 3/8 60	500 227								
1 1/8	29	5411835	076374	9 1/2	8618	1/4 6	1/16 2	1 1/4 32	4 1/4 108	1 13/16 46	2 15/16 75	2 5/8 67	710 322								
1 1/4	32	5412035	076398	12	10886	1/4 6	1/16 2	1 3/8 35	4 1/2 114	2 51	3 1/4 83	3 76	1000 454								
1 3/8	35	5412235	076411	13 1/2	12247	1/4 6	1/8 3	1 1/2 38	5 1/4 133	2 1/4 57	3 1/2 89	3 1/4 83	1300 590								
1 1/2	38	5412435	076435	17	15422	1/4 6	1/8 3	1 5/8 41	5 3/4 146	2 3/8 60	3 7/8 98	3 1/2 89	1600 726								
1 3/4	44	5412835	076466	25	22680	1/4 6	1/8 3	2 51	7 178	2 7/8 73	4 3/4 121	4 102	2850 1294								
2	51	5413235	076480	35	31752	1/2 13	1/8 3	2 1/4 57	7 3/4 197	3 1/4 83	5 3/4 146	4 7/8 124	4000 1816								
2 1/2	64	5414035	076527	55	49896	1/2 13	1/8 3	2 3/4 70	10 9/16 268	4 1/8 105	7 1/4 184	5 1/2 140	9000 4086								

Anchor Shackles - Screw Pin Drop-Forged Carbon Steel Galvanized - Bagged, 1 per Bag, 10 Bags per Carton

Size		Cat. No.	UPC No. 020418	Working Load Limit		Tolerances Length		Tolerances Width		B		C		D		E		F		Weight/ Shelf Pack	
in.	mm			ton	kg	±in. ±mm	±in. ±mm	±in. ±mm	±in. ±mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lb	kg
1/4	6	B5960435	154928	1/2	454	1/16 2	1/16 2	5/16 8	1 1/8 29	15/32 12	25/32 20	11/16 17	2 0.9								
5/16	8	B5960535	156687	3/4	680	1/16 2	1/16 2	3/8 10	1 1/4 32	17/32 13	27/32 21	3/4 19	2.7 1.2								
3/8	10	B5960635	154942	1	907	1/8 3	1/16 2	7/16 11	1 7/16 37	21/32 17	31/32 25	15/16 24	4.2 1.9								

Anchor Shackles - Screw Pin Drop-Forged Carbon Steel Galvanized - Loose, 10 Shackles per Box

Size		Cat. No.	UPC No. 020418	Working Load Limit		Tolerances Length		Tolerances Width		B		C		D		E		F		Weight Per Box	
in.	mm			ton	kg	±in. ±mm	±in. ±mm	±in. ±mm	±in. ±mm	in.	mm	in.	mm	in.	mm	in.	mm	in.	mm	lb	kg
1/4	6	5410434	076152	1/2	454	1/16 2	1/16 2	5/16 8	1 1/8 29	15/32 12	25/32 20	11/16 17	1.3 0.59								
5/16	8	5410534	076183	3/4	680	1/16 2	1/16 2	3/8 10	1 1/4 32	17/32 13	27/32 21	3/4 19	2.1 0.95								
3/8	10	5410634	076213	1	907	1/8 3	1/16 2	7/16 11	1 7/16 37	21/32 17	31/32 25	15/16 24	3 1.36								
7/16	11	5410734	076244	1 1/2	1361	1/8 3	1/16 2	1/2 13	1 3/4 44	23/32 18	1 5/32 29	1 1/8 29	5 2.27								



ADVERTENCIA

Para prevenir la posibilidad de lesiones graves:

- NO EXCEDA el límite de carga de trabajo (WLL).
- NO LA UTILICE choque o golpee la carga.
- NO USE el accesorio si se ve deformado o desgastado.



WARNING

To prevent the possibility of serious bodily injury:

- DO NOT EXCEED the working load limit.
- DO NOT shock or impact load.
- DO NOT USE if the fitting is visibly distorted or worn.

TRANSCAT®



Visit us at Transcat.com!

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001