

Waterproof Palm pH Meter

Big Digit LCD display in rugged housing with choice of stick or cabled pH Electrode

Features:

- Large LCD displays pH or mV and Temperature simultaneously
- Microprocessor provides for Automatic Buffer recognition
- Memory stores 15 readings
- Automatic Temperature Compensation via Pt-100 sensor built into electrode
- Unit is completely waterproof when electrode is connected to the meter
- Rugged design for handheld or wall mount (magnetic back)
- Magnetic back panel offers optimum flexibility and convenience
- Low Battery indicator and Auto Power off
- Specifically designed for fast response measurement
- Select PH220-C Kit to include ATC pH polycarbonate electrode (12mm diameter) with 39" (1m) cable
- Select PH220-S Kit to include ATC pH stick type polycarbonate electrode (12mm diameter) for direct connection to meter
- Includes protective rubber holster with magnetic back, pH electrode with cable, direct pH electrode, pH 4 and pH 7 buffers, and 9V battery



PH220-C includes pH electrode with 39" (1m) cable.



6015WC pH electrode with 39" (1m) cable with 4-pin connector



6012WS Stick pH Electrode (4-pin connector)



Specifications	
pH range:	0.00 to 14.00pH
Temperature range:	32 to 212°F (0 to 100°C)
Max resolution:	0.01pH, 0.1°
Basic Accuracy:	±0.01pH, ±0.8°F/0.5°C
Dimensions:	4.4x3.1x1.5" (111x79x39mm)
Weight:	9.2oz (260g)

Ordering Information:

PH220-C.....Waterproof Palm pH Meter with cabled pH electrode
PH220-S.....Waterproof Palm pH Meter with stick pH electrode
6015WCWaterproof pH electrode with cable for Palm pH Meter
6012WSWaterproof stick type pH electrode for Palm pH Meter
PH103.....Tripak buffer pouches (6ea. 4, 7, 10pH, 2 Rinse solution)
650470.....Tripak buffer capsules (3 vials - 10ea. of 4, 7, 10pH)
6015WCWaterproof pH Electrode with cable for Palm pH
6012WSWaterproof Stick Type pH Electrode for Palm pH

EXTECH INSTRUMENTS CORPORATION
285 Bear Hill Road, Waltham, MA 02451-1064
Phone: 781-890-7440 • FAX 781-890-7864
ISO 9001:2001 CERTIFIED

Make mine an Extech!
www.extech.com



07/03 - R1