



## NEW 798 Series Electronic Calipers

0-12" / 0-300mm

- Large, easy to read LCD, .310" character height
- IP67\* level of protection against coolant, water, dirt and dust
- Induction type linear encoder system
- Data Output- Patented non-contact RS-232
- Heavy-duty bar and slide, 3.5mm thick
- Hardened stainless steel measuring surfaces for long life
- Fine adjustment
- Slide lock
- Linear accuracy meets DIN862
- .0005" (0.010mm) resolution
- CR2032 3V battery (> 1 year battery life under normal use)
- In/mm conversion
- Zero at any position
- Automatic shutoff of the display after 30 minutes of non-use
- Reactivation of display with movement of slide with no loss of position
- 798B Calipers output data to Starrett SPC Plus hardware and software and to PCs and work well with Starrett Datasure® Wireless Data Collection Systems



According to IEC60529, IP67 stands for:

- The first number "6" identifies protection against ingress of dust
- The second number "7" identifies protection against submersion in water under standardized conditions of pressure for 30 minutes.



798 Electronic Calipers			
Range	Description	Catalog No.	EDP
0-6" (150mm)	Caliper with Output in Fitted Plastic Case	798B-6/150	12521
	Caliper with Output, Standard Letter of Certification†, in Fitted Plastic Case	798B-6/150 W/SLC	12522
	Caliper without Output in Fitted Plastic Case	798A-6/150	20798
0-8" (200mm)	Caliper with Output in Fitted Plastic Case	798B-8/200	12523
	Caliper with Output, Standard Letter of Certification†, in Fitted Plastic Case	798B-8/200 W/SLC	12524
	Caliper without Output in Fitted Plastic Case	798A-8/200	20799
0-12" (300mm)	Caliper with Output in Fitted Plastic Case	798B-12/300	12525
	Caliper with Output, Standard Letter of Certification†, in Fitted Plastic Case	798B-12/300 W/SLC	12526
	Caliper without Output in Fitted Plastic Case	798A-12/300	20800

**Accessories, Cables and Case Information for 798 Electronic Calipers**

Description	Catalog No.	EDP
Center Distance Attachment	PT26151	64440
Depth Attachment	PT22431	64640
Non-contact Computer Interface Cable to PC (USB) with Driver CD	PT63329	12732
Replacement Non-contact Computer Interface Cable to PC (USB)	PT63329-1	12733
Two 3-Volt Batteries, CR2032	PT99492	65650
Deluxe Padded Case for 0-6" (150mm) Calipers	723ZZ-6/722ZZ-6	57070
Finished Wood Case for 0-8" (200mm) Calipers	950	63878
Finished Wood Case for 0-12" (300mm) Calipers	946	56695

† Includes redemption card for Standard Letter of Certification (SLC).

**Approximate Jaw Depths for 798 Electronic Calipers**

	6" (150mm)	8" (200mm)	12" (300mm)
<b>Outside</b>	1-1/2" (38mm)	1-7/8" (47.6mm)	2-1/2" (63.5mm)
<b>Inside</b>	5/8" (16mm)	3/4" (19mm)	3/4" (19mm)