

All Products

Automotive Products

Basic Electrical Testers

Cable Testers

Calibrators

Clamp Meters

Comm. Test Tools

Data Acquisition

Digital Multimeters

Gas Measurement

Network Products

Power Supplies

Oscilloscopes

RCL Meters

Process Products

Power Quality Tools

Scopemeters

Thermometers

Signal Sources

Timer/Counters

TV Generators

80i-110s



[Visit us at Transcat.com!](#)

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001

Clamp-on AC/DC Current Probe

Accurate AC, DC and AC+DC current measurements for electrical and electronic applications. Wide measurement range from 50 mA to 100A - useful to 10 mA. The 80i-110s has a safety designed 600V insulated BNC, compatible with Fluke 40 and 41 Power Meters, ScopeMeter test tools and oscilloscopes. 2 Switch Selectable Input Ranges: 0..10A, 0..100A Basic accuracy: \pm (3% of reading + 50 mA) Output Signal: 100 mV/A, 10 mV/A Frequency Range: DC..100 kHz Working Voltage: 600V AC rms Maximum Conductor Size: 11.8 mm (0.46") diameter Safety Rating: 600V rms Overvoltage Installation CAT II and 300V rms Overvoltage Installation CAT III, per IEC 1010-02-032. BB120 Shielded Banana to BNC Adapter is required to adapt to ScopeMeter 120 series shielded banana jack inputs.

Product	Limitations
105B	None
123	None
39	None
41B	None
92B	None
96B	None
99B	None

[Return to Meter Selection Tool](#)