



# INTEGRA®

## SPECIAL FEATURES:

- Single lens and adjustable temples ensure reliable performance.
- Replacement lens extends the life of each pair.
- Select frames available with ratchet adjustment temples.
- Select frames available with fog-free coating.
- Lenses are coated for superior scratch resistance.
- Lenses provide 99% protection against harmful UV rays.

## GENERAL SPECIFICATIONS

Lens Thickness:	2.0mm	PD	68 mm
Lens Base	4.0 curve	Weight	35 gm
Lens size vertical	39mm	Lens Size Diagonal	138mm
Bridge	n/a	Temple length (lens-tip)	85mm

Overall Width (hinge-hinge) 149mm

## FRAME AND LENS OPTIONS:

- Frame colors:
  - o Black, Blue, Blue/White/Red, Yellow/Black, Red
- Lens options:
  - o Clear, Grey, Amber, Vermilion, Silver Mirror, 2.0 IR Filter, 3.0 IR Filter, 5.0 IR Filter, Indoor/Outdoor Mirror, Clear Anti-fog, Grey Anti-fog

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	4 curve, wrap around w/integral side shield
Frame	Nylon 6.6	lens removable from frame
Side Shield	Polycarbonate	integral to lens
Nose piece	Polycarbonate	integral to lens
Sleeve (on temple)	Nylon 6.6	adjustable to 4 positions
Temple	Nylon 6.6	adjustable
Temple tip	n/a	n/a
Hinge	Polycarbonate	3 barrel type, integral to frame sleeve
Screw	Nickel plated	standard hinge screw

## MARKINGS

Lens: As per standard

Frame: As per standard

## PACKAGING

1 pc in a polybag; 12 pcs in an inner box; 300 pcs in a case

## STANDARDS

MEETS ANSI Z87.1-2003 HIGH IMPACT STANDARDS and CE EN 166 CERTIFIED  
SEI CERTIFIED to CSA Z94.3 – 2002 TEST RESULTS AVAILABLE UPON REQUEST