

Part No.

2T2T-HOS-3ft

Quick-connect hose with 1/4" Quick-connect tube hose, 3 feet long

Hoses permit connections to Quick-test adapters, tube fitting quick-connects or NPT quick-connects

Features

- Low volume reduces the pumping effort or compressed gas usage in pressure calibration
- No thread sealant required – connect adapters to without wrenches, thread sealant or thread tape
- Bubble tight connections to 6900 psi (brass) or 11,040 psi (stainless steel) with no moving parts
- No moving parts reduces maintenance to almost zero
- Hose is hard to break and very flexible
- Adapt from hose to virtually any device under test with only one connection
- Silver color dramatically reduces the effect that changing temperature has on pressure stability
- A strain-relief on each hose end reduces wear and dramatically increases hose life
- Made in U.S.A.
- Connect to any tube fitting without using a wrench
- Ideal for use with Oxygen analyzers or other applications where connecting to



2T2T-HOS-3ft

Specifications

Length	3 ft
Pressure Range	0 to 6900 psi (0 to 475 bar)
Burst Pressure	27000 psi (1,860 bar)
End 1	1/4" Tube stub, stainless steel
End 2	1/4" Tube stub, stainless steel
Temperature range	-40 to 140 °F (-40 to 60 °C)
Outer Diameter	0.2 in (5.1 mm)
Inner Diameter	0.08 in (2.0 mm)
Minimum Bend Radius	1 in (25.4 mm)
Color	Silver
Construction	Polyamide core tube, High tensile synthetic fiber and polyamide outer cover
End materials	Stainless Steel
Fluid Media	Water, Petroleum Based Oil, Air, Inert Gas