Part No

LC10-GA2M

LC10 Vacuum gauge, 30Hg / 780 mmHg, 1/4" Male NPT bottom connection

The LC10 is a robust device that measures and displays pressure readings on a large, backlighted screen. The LC10 has the ability to show High and Low pressure values on-screen, change between 15 different engineering units or add custom engineering units. The included PC FieldLab Desktop software can be used for calibration, testing and live viewing of pressure.



LC10-GA2M

Specs/Attributes

2
1500 Hours
AA Alkaline (LR6)
20 PSI / 2 bar / 200 kPa
Certified to CSA Standard C22.2 No. 61010-1, Conforms to UL / IEC / EN / AS Standard No. 61010-1, Complies with Pressure Equipment Directive 2014/68/EU, Complies with Low Voltage Directive 2014/35/EU, Complies with Electromagnetic Compatibility Directive 2014/30/EU
USA
50 mA @ 5 VDC
atm, bar, cmH2O @4°C, inH2O @39°C, kPa, mbar, psi, inHg @39°F, kgf / cm^2, mmHg @0°C, Pa, mmH2O @4°C, ftH2O @39°F, cmHg @ 0°C, oz / sqin
IP67 (1 meter water submersion for 30 minutes)
2.4 in / 61 mm segmented LCD Display
ABS / Polycarbonate Blend, Powder Coated Aluminum
165 °F / 75 °C
120 °F / 50 °C
30 InHg / 101.6 kPa
Gauge Vacuum
+/- 0.25% of Full Scale (ASME Grade 3A/ISO Class 0.25)
Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water



Specs/Attributes

Min Storage Temperature	-40 °F / -40 °C
Min Temperature	-4 °F / -20 °C
Operating Altitude (max)	10,000 ft (3050 m)
Process Connection	1/4" Male NPT
Protection Class	Pollution Degree 2 (UL / IEC 61010-1)
Relative Humidity	0% to 90% (-10 to 35°C), 0% to 70% (35 to 50°C)
USB Connection	USB (Micro B)
Wetted Materials	316 Stainless Steel
Wrench Size	7/8 In 23 mm
Weight	12.6 oz / 355 grams
Dimensions	H: 1.75 in (4.45 cm) x W: 3.4 in (8.64 cm) x D: 4.1 in (10.41 cm)