

Part No.

# NPAK-TRS0

*Liquid trap with male Quick-test top port, female Quick-test bottom port*

Eliminates unwanted fluid or moisture that can contaminate any gas system.

## Features

- Quick-release lid allows for easy cleaning of dirt or liquid without tools
- Entraps fluid and debris out of system to prevent blocking or plugging
- High pressure trap is ideal for pneumatic systems
- Compatible with all Ralston Instruments Quick-test hoses and adapters

## Item Includes

- Assembly - TRAP Assembly (TRAP)
- Top Connection - Male Quick-test outlet port, S.S. (QTHA-3SS0)
- Bottom Connection - Female Quick-test outlet port with drain tube (for NPAK-TRS0), S.S. (QTHA-3SSA-LD)



NPAK-TRS0

## Specifications

|                   |                                                              |
|-------------------|--------------------------------------------------------------|
| Pressure Range    | 0 to 3000 psi (0 to 207 bar)                                 |
| Temperature range | 0 to 130 °F (-18 to 54 °C)                                   |
| Construction      | Anodized Aluminum, Stainless Steel                           |
| Seal materials    | Buna-N, Teflon                                               |
| Weight            | 1.139375 lb (0.5 kg)                                         |
| Dimensions        | H: 5.5 in (13.97 cm) x W: 2 in (5.08 cm) x D: 2 in (5.08 cm) |