

Part No.

QTHP-2FBA

5kpsi / 35 MPa Hydraulic hand pump, 2 Quick-test outlet ports, 3 ft hose, 1/4" FNPT gauge conn., 1/4" MNPT Process conn.

5kpsi / 35 MPa Hydraulic hand pump, 2 Quick-test outlet ports, 3 ft hose, 1/4" FNPT gauge conn., 1/4" MNPT Process conn.



QTHP-2FBA

Included Items

- Hand Pump - QTHP 5000 psi / 35 MPa Hydraulic Pump (QTHP)
- Reference Connection - 1/4" female NPT x female Quick-test, no check-valve, brass (QTHA-2FBA)
- Process Connection - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Hose - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)

Specs/Attributes

| | |
|----------------------|--|
| Hose 1 | Quick-test Hose, Stainless Steel ends, 3ft / 0.9m long |
| Process Connection | 1/4" Male NPT |
| Reference Connection | 1/4" Female NPT |
| Country of origin | USA |
| Weight | 3.25 lbs / 1.47 kg |
| Dimensions | H: 5.7 in (14.48 cm) x W: 6 in (15.24 cm) x D: 8.6 in (21.84 cm) |

Hand Pump QTHP

| | |
|----------------|--|
| Outlet Port | Male Quick-test, Male Quick-test with cap and chain |
| Pressure Media | Liquid |
| Materials | Anodized Aluminum, Brass, Stainless Steel, Polysulfone |

Hand Pump QTHP

| | |
|----------------------------|--|
| Max Pressure | 5000 PSI / 345 bar / 35 MPa |
| Media Compatibility | Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Mineral Oil, Petroleum Based Oil, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil |
| Seal Materials | Buna-N, Teflon |
| Fine Adjustment Resolution | 0.01 PSI / 0.07 mbar / 0.07 kPa |
| Min Temperature | -29 °F / -34 °C |
| Country of origin | USA |
| Max Temperature | 140 °F / 60 °C |
| Weight | 2.93 lbs / 1.33 kg |
| Dimensions | H: 5.7 in (14.48 cm) x W: 6 in (15.24 cm) x D: 10.6 in (26.92 cm) |

Reference Connection QTHA-2FBA

| | |
|-------------------|---|
| Country of origin | USA |
| Has Check Valve | No |
| Materials | Brass |
| Max Pressure | 5000 PSI / 345 bar / 35 MPa |
| Max Temperature | 225 °F / 105 °C |
| Max Vacuum | 0.00 InHg / 0.0 kPa |
| Wrench Size | 3/4 In 19 mm |
| Dimensions | H: 1.52 in (3.86 cm) x W: 0.75 in (1.91 cm) |

Process Connection QTHA-2MB0

| | |
|-------------------|---|
| Country of origin | USA |
| Has Check Valve | No |
| Materials | Brass |
| Max Pressure | 5000 PSI / 345 bar / 35 MPa |
| Max Temperature | 225 °F / 105 °C |
| Max Vacuum | 0.00 InHg / 0.0 kPa |
| Min Temperature | 0 °F / -18 °C |
| Seal Materials | Buna-N |
| Wrench Size | 9/16 In 15 mm |
| Dimensions | H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm) |

Hose QTQT-HOS-3ft

| | |
|-------------------|---|
| Burst Pressure | 27000 PSI / 1860 bar / 185 MPa |
| Color | Silver |
| Country of origin | USA |
| Fluid Media | Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water |
| Inner Diameter | 0.08 In / 3.00 mm |

Hose QTQT-HOS-3ft

| | |
|---------------------|-----------------------------|
| Length | 3 ft / 92 cm |
| Materials | Brass |
| Max Pressure | 6900 PSI / 475 bar / 48 MPa |
| Max Temperature | 140 °F / 60 °C |
| Max Vacuum | 0.00 InHg / 0.0 kPa |
| Min Temperature | -40 °F / -40 °C |
| Minimum Bend Radius | 1.00 In / 26 mm |
| Outer Diameter | 0.20 In / 6.00 mm |
| Type | QT |