

Part No.

# QTHR-QT-100ft

Quick-test Hose Reel with 100ft Quick-test hose, brass hose ends

The Quick-test hose reel is an innovative solution for storing Ralston Quick-test hoses. It includes inlet and outlet ports, a brake and locking pin and multiple mounting options.



QTHR-QT-100ft

#### **Included Items**

- Hose Reel Quick-test Hose Reel without hose (QTHR-0000)
- Hose Quick-test 6900 psi hose, brass hose ends, 100ft long (QTQT-HOS-100ft-NR)

### Hose Reel OTHR-0000

Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Operating Temperature	140 °F / 60 °C
Materials	Anodized Aluminum, Brass, Powder Coated Steel, Stainless Steel
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Weight	5.08 lbs / 2.30 kg
Dimensions	H: 9.5 in (24.13 cm) x W: 6.5 in (16.51 cm) x D: 11.5 in (29.21 cm)

### Hose QTQT-HOS-100ft-NR

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver



## Hose QTQT-HOS-100ft-NR

Country of origin	USA
Fluid Media	Air,Inert Gas,Natural Gas,Petroleum Based Oil,Water
Hose Length	100 ft / 30.48m
Inner Diameter	0.08 ln / 3.00 mm
Length	50 ft / 16 m
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 ln / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Туре	QT
Weight	1.19 lbs / 540 grams