



SnakeEye™

Specifications

TRANSCAT

Visit us at [Transcat.com!](http://Transcat.com)

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001

Display Unit	<ul style="list-style-type: none">• 5 in (12.7 cm) color TFT-LCD• 320 x 234 color pixels• Rotatable• Anti-glare screen• Adjustable hand strap• Backlight brightness adjustment High/Low• Camera probe light control On/Off• External power port• Video I/O port• Water resistant
Camera	<ul style="list-style-type: none">• CCD camera• 1.2 in (3.0 cm) diameter• Removable• Sensitivity 10 lux• Resolution 512 x 492• Field of view 46 degrees• 4 White light LEDs• Water proof to 100 ft (30m)
Power System	<ul style="list-style-type: none">• Up to 90 min continuous operation• 2 x 6 V NiMH rechargeable batteries• Battery fast charger• AC/DC adapter• 12 V auto adapter
Camera Adapters	<ul style="list-style-type: none">• 18 in (45.7 cm) length• 90 degree one way articulation• Sure-grip handle

C-Mount Camera

- Adapts SnakeEye to fiberscopes and borescopes

Attachments

- 4 ft (1.2 m) flexible cable
- Carrying case
- Video I/O cable

General

- Total system weight- less than 2.5 lbs (1.1 kg)
- Power requirements: AC Nominal input: 100-240 V, DC nominal input: 12V
- System operating temperature- 32 degrees F to 122 degrees F (0 degrees C to 50 degrees C)
- Video input/output- NTSC