

PLARAD[®]
Torque & Tension Systems

XB Hydraulic Power Packs



Compact hydraulic power packs



Robust industrial frame for protection on rough assignments

Use of single or multiple hydraulic torque wrench for single or twin hose applications

Mechanism for winding up cables

The solenoid switch is in the protected range

The external oil filter (on the XB 2 and XB 3,5) and the service-friendly construction allow easier maintenance work

Improved valve technology





- Its light weight makes the XB 1 a miniature powerhouse and an ideal power pack for mobile service.
- The all-rounder of the XB Series is the XB 2. It features a constant flow rate of 1.25 l/min up to ultimate pressure.
- With a constant flow rate of 3.5 l/min up to ultimate pressure, the XB 3.5 is a high performance power pack, particularly suitable for very extensive bolting operations.
- Other hydraulic tools, such as flange spreaders and nut splitters, can also be powered.

Type	Flow rate	Weight	Pressure
XB 1	0,8 l/min 0.21 gal/min	19 kg 42 lb	max. 800 bar max. 11.600 psi
XB 2	1,2 l/min 0.32 gal/min	29 kg 64 lb	max. 800 bar max. 11.600 psi
XB 2-Z	8,0 / 1,2 l/min 2.11/0.32 gal/min		max. 800 bar max. 11.600 psi
XB 3.5	3,5 l/min 0.92 gal/min	33 kg 73 lb	max. 800 bar max. 11.600 psi
XB-VAX 2	1,2 l/min 0.32 gal/min	29 kg 64 lb	max. 800 bar max. 11.600 psi
XB-VAX 3.5	3,5 l/min 0.92 gal/min	33 kg 73 lb	max. 800 bar max. 11.600 psi

PLARAD[®]
Torque & Tension Systems



Maschinenfabrik Wagner GmbH & Co. KG
Birrenbachshöhe · D-53804 Much · Germany

Phone (national): (02245) 62 – 0
Fax (national): (02245) 62 – 66

Phone (international): +49 (0)2245 62 – 10
Fax (international): +49 (0)2245 62 – 22

E-mail: info@plarad.com
Web: <http://www.plarad.com>

This document or parts thereof may only be reproduced or copied if prior written authorisation has been obtained. We reserve the right to make alterations. We accept no responsibility for printing errors or incorrect content.

Status: 04/2011 · EK 10387 - 123 EN