



HOBO[®] U26-001 Data Logger

Dissolved Oxygen Data Logger

Measure oxygen concentrations in lakes, streams, rivers, estuaries, and coastal waters with the HOBO U26 Dissolved Oxygen Data Logger. This affordable and precise data logger is recommended for aquatic biology and hydrology research projects. The HOBO U26 uses RDO[®] Basic (Rugged Dissolved Oxygen) optical DO sensor technology and is easy to maintain.



Includes:

- U26-001 data logger DO sensor cap Protective Guard
- Calibration Boot with sponge

Our HOBO U26 Dissolved Oxygen logger has been part of a multi-year evaluation of DO loggers and sensors by the Alliance for Coastal Technologies (ACT), and the results have been published online. This provides an un-biased report of how our U26 performs in lab and field conditions. Note that our response letter with our added recommendations is attached at the end of this report on pages 58 and 59.

[Click here to read.](#)

Supported Measurements:

Dissolved Oxygen and Temperature

Key Advantages:

- Affordable, high performance dissolved oxygen (DO) monitoring with 0.2 mg/L accuracy
- Optical DO sensor technology for long-lasting calibration with less maintenance
- HOBOware Pro's Dissolved Oxygen Assistant software corrects for measurement drift from fouling; provides salinity-adjusted DO concentrations and percent saturation
- Optical USB interface for high-speed, reliable data offload
- Easy-to-replace DO sensor cap lasts six months

NOTE: For DO measurements in saltwater, an adjustment for salinity is required. For waters with small changes in salinity (<2 ppt), a salinity meter reading typically provides enough accuracy. For environments with greater salinity changes, we generally recommend the HOBO U24-002-C conductivity logger . If you need DO in Percent Saturation, barometric pressure data is required, which can be logged with a HOBO Water Level Data Logger (U20-001-04).

HOBO U26-001 Data Logger Specifications

Dissolved Oxygen

Sensor Type:	Optical
Measurement Range:	0 to 30 mg/L
Calibrated Range:	0 to 20 mg/L; 0 to 35°C (32 to 95°F)
Accuracy:	± 0.2 mg/L up to 8 mg/L; ± 0.5 mg/L from 8 to 20 mg/L
Resolution:	0.02 mg/L
Response Time:	To 90% in less than 2 minutes
DO Sensor Cap Life:	6 months, cap expires 7 months after initialization

Temperature

Temperature Measurement/Operating Range:	-5 to 40°C (23 to 104°F); non-Freezing
Temperature Accuracy:	0.2°C (0.36°F)
Temperature Resolution:	0.02°C (0.04°F)
Response Time:	To 90% in less than 30 minutes

Logger

Memory:	21,700 sets of DO and temperature measurements (64 KB total memory)
Logging Rate:	1 minute to 18 hours
Time Accuracy:	±1 minute per month at 0 to 50°C (32 to 122°F)
Battery:	3.6 V lithium battery; factory replaceable
Battery Life:	3 years (at 5 minute logging)
Download Type:	Optical
Depth Rating:	100 m (328 ft)
Wetted Materials:	Black Delrin®, PVC, EPDM o-rings, silicone bronze screws; rated for saltwater use
Size:	39.6 mm diameter x 266.7 mm length (1.56 x 10.5 inches)
Weight:	464 g (16.37 oz)
Environmental Rating:	IP68



The CE Marking identifies this product as complying with all relevant directives in the European Union (EU).

Contact Us

Sales (8am to 5pm ET, Monday through Friday)

- ▶ Email sales@onsetcomp.com
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-800-564-4377
- ▶ Fax 1-508-759-9100

Technical Support (8am to 8pm ET, Monday through Friday)

- ▶ Contact Product Support www.onsetcomp.com/support/contact
- ▶ Call 1-508-759-9500
- ▶ In U.S. toll free 1-877-564-4377

Onset Computer Corporation
470 MacArthur Boulevard
Bourne, MA 02532