## PORTABLE BRIDGES & DECADE RESISTANCE BOXES

2755



Portable Wheatstone Bridge Murray and Varley loop tester Self-contained power source

2769



Portable Kelvin Double Bridge Simple to operate Built-in standard resistors

Model	2755	2769
Measuring Range:	275597: 1.000 $\Omega$ to 10.00M $\Omega$	276910: 0.1mΩ to 110 Ω
Measuring Dials:	1Ω, 10Ω, 100Ω, 1000Ω (all X 10)	1.00Ω to 11.00Ω at x 1
Multipliers:	X 0.001,0.01,0.1,1,10,100,1000	X 0.0001*,0.001,0.01,0.1,1,10
Accuracy:	Varies by range. Overall ±0.6% rdg.	$\pm$ (0.05 x multiplier + 0.01m $\Omega$ )
Temp. range:	5 to 35° C	5 to 35° C
Power Source:	3-1.5V DC batteries	2-1.5V DC(R20P) & 1-9V DC(6F22)
Power rating:	N/A	N/A
Size:	7½ x 9 x 4-¾"	7¼ x 9 x 4-¾"
Weight:	4.4 lbs.	5.7 lbs.
Accessories:	Carrying case	Carrying case
Optional	None required	*2771 standard resistor, 2753
accessories:		measuring cords, 2754 clamp device



