

EPSON TM-U220 Tape Printer



Approvals



Standard Features

- 9-Pin Dot Matrix print head
- High-speed 4.7 to 6.0 lines per second printing
- Drop-in paper set and auto paper loading
- Automatically transmits changes in printer status
- RS-232
- Optional connect-it cartridges for parallel, USB, 10 Base-T

TRANSCAT

▶ Visit us at Transcat.com!

35 Vantage Point Drive // Rochester, NY 14624 // Call 1.800.800.5001

Specifications

PRINT SPEED:

Approximately 4.7 lines per second

COLUMN CAPACITY:

40/42 or 33/35 columns

CHARACTERS PER LINE:

40 characters

PRINT AREA:

3" (76.2 mm) wide

CHARACTER FORMATION:

7 x 9 & 9 x 9 dot matrix

CHARACTER HEIGHT:

0.12 standard font

CHARACTER SET:

95 alphanumeric characters,
37 international characters,
128 x 12 graphic characters

LINE SPACING:

0.17" (4.32 mm)

PRINTHEAD LIFE:

Approximately 100 million strokes/pin

FORM THICKNESS:

0.002" to 0.003" (0.06 to 0.085 mm)

RIBBON:

Cassette-type purple ribbon. Ribbon life is approximately 1.5 million characters (continuous prints). Black ink also available.

SERIAL INTERFACES:

RS-232 compatible (25-pin D-sub)

BAUD RATES:

4800, 9600

PARITY:

7 or 8 bits, none, even or odd

STOP BITS:

1 or more

HANDSHAKING:

DTR/DSR or XON/XOFF control selectable

OVERALL DIMENSIONS:

Type A: 6.3" W x 11.3" D x 6.2" H
(160 mm W x 286 mm D x 157.5 mm H)
Type D: 6.3" W x 9.7" D x 5.4" H
(160 mm W x 248 mm D x 138.5 mm H)

APPROVALS:

UL listed, CSA-certified, CE marked

WARRANTY:

Two-year limited warranty (includes printhead)

EPSON TM-U295 Ticket Printer



Standard Features

- High-speed 1.9 to 2.3 lines per second printing
- Single copy or up to four-part multicopy ticket printing
- Functions in slave capacity, printing information sent via RS-232

Specifications

PRINT SPEED:

1.9 to 2.3 lines per second (5 x 7 character, 3 dot line spacing)

COLUMN CAPACITY:

35/42 columns

CHARACTERS PER LINE:

35 standard font

PRINT AREA:

2.59" W (65.8 mm W)

CHARACTER FORMATION:

5 x 7 and 7 x 7 dot matrix

CHARACTER HEIGHT:

0.11 standard font

CHARACTER SET:

Full 96-character ASCII; with software control, 32 international characters, 128 x 2 graphic characters

LINE SPACING:

0.16" (4.06 mm) software programmable in 1/60" units

PRINTHEAD LIFE:

Approximately 100 million strokes/pin

FORM THICKNESS:

Single-ply - 0.003" to 0.009" (0.08 to 0.23 mm)
Copy paper - 0.003" to 0.014" (0.08 to 0.36 mm)

RIBBON:

Cassette-type purple ribbon. Ribbon life is approximately 1.5 million characters (continuous prints). Black ink also available.

SERIAL INTERFACES:

RS-232 compatible (25-pin D-sub)

BAUD RATES:

1200, 2400, 4800, 9600, selectable

PARITY:

7 or 8 bits, none, even or odd

STOP BITS:

1 or more

HANDSHAKING:

DTR/DSR or XON/XOFF control selectable

OVERALL DIMENSIONS:

7.08" W x 7.49" D x 3.99" H
(180 mm W x 190.5 mm D x 101.5 mm H)

APPROVALS:

UL listed, CSA certified, CE marked

WARRANTY:

One-year limited warranty (includes printhead)

Specifications subject to change without notice

RICE LAKE
WEIGHING SYSTEMS
Commitment Beyond Measurement®

