



**OIML E2  
316L SS**

[VIEW >](#)

**OIML Class E2** - Can be used as a reference standard in calibrating other weights and is appropriate for calibrating high-precision analytical balances with a readability as low as 0.1 mg to 0.01 mg.

Class	Nominal Value	Accuracy (mg)	Material	Shape
E2	1mg	0.006	316L Stainless Steel	Flat
E2	2mg	0.006	316L Stainless Steel	Flat
E2	5mg	0.006	316L Stainless Steel	Flat
E2	10mg	0.008	316L Stainless Steel	Flat
E2	20mg	0.010	316L Stainless Steel	Flat
E2	50mg	0.012	316L Stainless Steel	Flat
E2	100mg	0.016	316L Stainless Steel	Flat
E2	200mg	0.020	316L Stainless Steel	Flat
E2	500mg	0.025	316L Stainless Steel	Flat
E2	1g	0.03	316L Stainless Steel	Cylindrical/Knob
E2	2g	0.04	316L Stainless Steel	Cylindrical/Knob
E2	5g	0.05	316L Stainless Steel	Cylindrical/Knob
E2	10g	0.06	316L Stainless Steel	Cylindrical/Knob
E2	20g	0.08	316L Stainless Steel	Cylindrical/Knob
E2	50g	0.10	316L Stainless Steel	Cylindrical/Knob
E2	100g	0.16	316L Stainless Steel	Cylindrical/Knob
E2	200g	0.3	316L Stainless Steel	Cylindrical/Knob
E2	500g	0.8	316L Stainless Steel	Cylindrical/Knob
E2	1kg	1.6	316L Stainless Steel	Cylindrical/Knob
E2	2kg	3.0	316L Stainless Steel	Cylindrical/Knob
E2	5kg	8.0	316L Stainless Steel	Cylindrical/Knob
E2	10kg	16	316L Stainless Steel	Cylindrical/Knob
E2	20kg	30	316L Stainless Steel	Cylindrical/Knob

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)

[VIEW >](#)