

STANDARD FEATURES

- Push-button zero adjust
- Max/min memory
- Selectable engineering units
- Variable damping
- Tare
- Port select
- Push-to-print
- RS232 I/O
- High static DP capability

OPTIONAL FEATURES

- Backlit display
- Rechargeable battery pack

The Ashcroft® PTIndicator is an extremely versatile pressure measurement and test instrument. It can simultaneously display the output of two pressure sensors, two RTD's or one of each. It offers 12 standard user selectable engineering units and one custom value. Other dedicated front panel buttons make it easy to set zero, check max/min values, adjust measurement damping, select either or both ports for standard display, additive or differential display, print the display and configure the RS232 output. All front panel features are accessible via the RS232 port for remote configuration or data acquisition.

**NOW AVAILABLE
IN 0.025%
ACCURACY!**



PRODUCT SPECIFICATIONS

PHYSICAL SPECIFICATIONS

Dimensions

7.72 in. (L) x 6 in. (W) x 2.95 in. (H)

Panel Cutout

5.4 in. x 2.68 in.

Weight

Depending on configuration

Max. <4 lbs. w/2 sensors and battery pack

Case Material

High impact ABS

Sensor Capacity

2 bays for Ashcroft PPT sensors

Display

2 line LCD, 0.038 in. height per line. Can display simultaneous readings from 2 modules.

Options

Backlit Display

Built-in NiCad Rechargeable Battery Pack

Handle

Panel Mounting Brackets

OPERATING SPECIFICATIONS

Operating Temperature Range

32° to 120°F

Storage Temperature

-4° to 158°F

Update Rate

130 ms (nominal) with one sensor installed

Resolution

±0.002% of span, 60,000 counts (max)

Power Requirements

Standard: ac adapter provided for 110Vac/60 Hz

Available: ac adapter provided for 220Vac/50 Hz

ac adapter provided for 100Vac/60 Hz

Optional: Built-in rechargeable NiCad Battery Pack*

* (Life: 25 hours nominal without backlit LCD, 5 hours nominal with backlit LCD. Activating RS232 results in approximately 30% reduction in battery life.)

Certification

N.I.S.T. Traceable certification document provided for base display unit and sensor modules

PRESSURE SENSOR SPECIFICATIONS

PPT-1

Pressure Types

Gauge, differential and compound

Available Ranges

(See Chart)

Available Accuracies

±0.06 (0/2-0/200 in. H₂O), ±0.07 (0/0.25-0/1 in. H₂O) or 0.1% of Span

Compensated Temperature Range

20°F to 120°F

Temperature Effect

±.004% of Span per °F over compensated range (from reference temperature range of 70° ±3°)

Repeatability

±0.01% of span (range 0/1 in. H₂O or higher)

±0.02% of span (ranges below 0/1 in. H₂O)

Sensitivity

±0.002% of span (typical)

Media Compatibility

Clean, dry, non-conductive, non-corrosive gas

Under/Overpressure Capability

-15 to 50 psi

Maximum Static (line) Pressure

100 psi

Process Connection

Standard: 1/8 NPT female

Optional: G 1/8 British standard

PPT-2

Pressure Types

Gauge, absolute, compound and vacuum

Available Ranges

(See Chart)

Available Accuracies

±0.025, 0.05 or 0.1 % of Span (±0.025 & 0.05% not available on 0/10,000 psi range)

Compensated Temperature Range

20°F to 120°F

Temperature Effect

Standard: ±.004% of Span per °F over the compensated range (from reference temperature range of 70° ±3°)

Optional: No additional error due to temperature over the compensated range

Repeatability

±0.01% of span

Sensitivity

±0.002% of span (typical)

Media Compatibility

0/5-0/10,000 psi ranges: Any medium compatible with 316 SS isolation.

Optional: Cleaned for Oxygen Service

Overpressure Capability

200% for ranges up to 1000 psi

150% for ranges over 1000 psi

Process Connection

Standard: 1/8 NPT female

Optional: 1/8 NPT female with flush port

(ranges 10 psi and over)

G 1/8 British standard

G 1/8 British standard with flush port

(ranges 10 psi and over)

Welded VCR fitting with standard

finish

Pressure Tester Model PT, Dual Display LCD Digital Pressure Indicator

RTD INTERFACE ASSEMBLY

PPT-RT1: Accommodates Pt100, Ni120, Cu120 and other common 2, 3 or 4 wire probes with resistance outputs of 400 ohms or less.
PPT-RT2: Accommodates Pt1000 and other common 2, 3 or 4 wire probes with resistance outputs of 4000 ohms or less.

Input Receptacle

Accepts TA4F type RTD connector

RTD Probes Available

Pt-100 probes, 6" or 12" length, with or without handle. DIN Class A accuracy. Includes mating TA4F connector. Consult factory for details and availability.



Rear view of Model PT
with 2 pressure sensors installed

STANDARD RANGES

PPT-2 psi (gauge and absolute pressure)	PPT-1 in. H ₂ O (gauge/ differential pressure)	Other Engineering Units**
5		
10	0.25*	psi
15	0.5*	in. H ₂ O
30	1.0*	in. Hg
50	2.0*	ftSW
60	3.0*	bar
100	5.0*	mbar
150	10*	kPa
200	15*	MPa
250	25*	mmHg
300	50*	cmH ₂ O
500	100*	mmH ₂ O
600	150*	kg/cm ²
1000	200*	User Selectable
1500		
2000		
2500		
3000		
5000		
6000		
7500		
10,000		
vacuum		
5		
10		
15		
compound		
±5		
±10	±0.125*	
±15	±0.25*	
-15/+30	±0.5*	
-15/+60	±1.0*	
	±1.5*	
	±2.5*	
	±5.0*	
	±7.5*	
	±12.5*	
	±25*	
	±50*	
	±75*	
	±100*	

**Note: Engineering units identified above are accessible through the unit select feature. However, readout will default to the primary unit of measure on start-up. Sensor modules scaled in primary units other than in. H₂O (PPT-1) or psi (PPT-2) are also available. Consult factory.

* Non-isolated, for clean dry gas only

TO ORDER

Base Display Unit

- 1) Specify Model: PT
- 2) Specify Power Requirements: 110, 220 or 100Vac
- 3) Specify Options: (Backlit, NiCad Battery Pack, Handle, Panel Mounting Brackets)

Sensors

(Base Display Unit can hold a total of 1 or 2 pressure sensors or RTD interface assemblies simultaneously. Sensors and interface assemblies will be installed into the base display unit at the factory.)

- 4) Type (PPT-1 or PPT-2)
- 5) Pressure Range and Unit of Measure (see range chart)
- 6) Pressure Type (see specifications)
- 7) Accuracy (see specifications)
- 8) Specify Options
 - a) "zero temperature error over compensated range" (PPT-2 only)
 - b) Optional fitting (see specifications)
 - c) Clean for Oxygen Service (PPT-2, 0/10-1/10,000 psi only)

RTD Interface Assembly

- 9) Type (PPT-RT1 or PPT-RT2)
- 10) Probe Type (when required. Consult factory for probe P/N)